



TRT

Tubeless Rim Taper



Automation of Rim Taping



SPECIFICATIONS :

Range :	20" to 32" wheels
Production capacity :	120 Wheels/hour depending on settings
Working air pressure :	6 bars – 90 PSI
Electrical connexion :	230 V – 400 VA
Power consumption :	13 liters/min
Weight :	180kg
Size :	0,9 x 0,8 x 1,7m

MAIN FEATURES :

- Overlap of the tape adjustable per single millimetre
- Automatic puncture of the valve hole
- Tape roll length up to 100m
- Wheel library for settings recall
- Compatible with several type of rim tape (polyester, polyimide)







OPTION :

- Additional set of rollers
- Rim tape supply

With more than 50 years of experience, **Mach1 Machinery** has given way to **Bikebotix** to offer you an even more comprehensive offer.

A global presence
French know-how 1971



-  **WHEEL BUILDING**
-  **MOTORCYCLE WHEEL BUILDING**
-  **RIM MANUFACTURING**
-  **BIKE ASSEMBLY**
-  **BIKE TOOLS**
-  **DATA MANAGEMENT**

Alongside expert and highly qualified development and customer service team 5 areas of expertise.

Proud to be a major player and a reference partner, BikeBotix exports worldwide solutions based on 4 fundamentals:

INNOVATION, PERFORMANCE, RELIABILITY and FLEXIBILITY.

BIKEBOTIX
SOLUTIONS IN MOTION

294 route des grands bois
74370 Villaz France
+33 450 220 639
machines@bikebotix.com
www.bikebotix.com